

100% Money Back
Guarantee

Vendor:VMware

Exam Code:2V0-622

Exam Name:VMware Certified Professional 6.5 – Data
Center Virtualization (6.5) Exam

Version:Demo

QUESTION 1

An administrator notices that a virtual machine running SQL Server is not performing as expected. Upon checking the logs, the administrator sees the following error: vmware.log> vmx| W110: NUMA and VCPU hot add are incompatible. Forcing UMA How can the administrator resolve this issue?

- A. Power off the virtual machine and disable vCPU hot plug.
- B. Reinstall VMware Tools.
- C. Modify the .vmx file to force NUMA and vCPU hot add to function.
- D. Install a third party plug-in to enable NUMA and vCPU hot add to function.

Correct Answer: A

QUESTION 2

Which two datapoints does VM Monitoring evaluate before resetting a virtual machine? (Choose two.)

- A. High CPU activity on the VM
- B. High CPU activity on the ESXi host running the VM
- C. Heartbeats sent from VMware Tools
- D. High memory utilization on the VM
- E. I/O activity

Correct Answer: CE

QUESTION 3

When using VMware Converter to import a Windows server and improve the consistency of the destination virtual machine, which optional step can be performed immediately prior to powering down the source server?

- A. Uninstall production applications.
- B. Perform a final synchronization task.
- C. Remove the server from the Active Directory domain.
- D. Remove the server from the network.

Correct Answer: B

QUESTION 4

An administrator is creating VMkernel adapters on an ESXi 6.5 host and wants to create separate VMkernel adapters for every type of traffic in the default TCP/IP stack. Which three types of traffic can be explicitly enabled on a separate VMkernel adapter? (Choose three.)

- A. Virtual SAN traffic
- B. NFS traffic
- C. vMotion traffic
- D. vSphere HA traffic
- E. Fault Tolerance logging traffic

Correct Answer: ACE

<https://docs.vmware.com/en/VMware-vSphere/6.5/com.vmware.vsphere.networking.doc/GUID-D4191320-209E-4CB5-A709-C8741E713348.html>

QUESTION 5

When installing vCenter Converter Standalone, why must an administrator perform a client-server installation instead of a local installation?

- A. to manage conversion tasks remotely
- B. to convert virtual machines as well as physical machines
- C. to allow installation of the Converter agent on remote source machines
- D. to hot clone physical or virtual machines

Correct Answer: A

QUESTION 6

Which two clients could an Administrator use to add a new identity source to the vCenter Single Sign-On domain? (Choose two.)

- A. vSphere Client
- B. Platform Services Controller Web Interface
- C. vSphere Appliance Management Interface
- D. vSphere Web Client
- E. VMware Host Client

Correct Answer: BC

QUESTION 7

To enable Predictive DRS, which three steps must be taken? (Choose three.)

- A. vRealize Log Insight must be enabled and configured to watch for Predictive DRS moves.
- B. The corresponding virtual machines must be tagged for Predictive DRS use.
- C. A supported version of vRealize Operations Manager must be configured and enabled.
- D. The Predictive DRS check box must be enabled.
- E. DRS must be enabled.

Correct Answer: CDE

QUESTION 8

Boot from SAN is supported on which three storage technologies? (Choose three.)

- A. iSCSI
- B. NFS 4.1
- C. FC
- D. VMware vSAN
- E. FCoE

Correct Answer: ACE

QUESTION 9

DRS is set to Fully-Automated mode and seems to be migrating virtual machines too frequently. Which action can potentially decrease the amount of automated migrations performed by DRS?

- A. Increase the Migration Threshold by moving the slider to the right.
- B. Decrease the Migration Threshold by moving the slider to the left.
- C. Set DRS to Partially-Automated mode.
- D. Enable EVC for the cluster.

Correct Answer: B

QUESTION 10

Which port is used for vSphere HA agent-to-agent communication?

- A. 902
- B. 443
- C. 8182
- D. 22

Correct Answer: C

QUESTION 11

Which storage feature always requires the use of third-party software on ESXi?

- A. Hardware Acceleration for NAS devices
- B. VVOL
- C. Hardware Acceleration for Block Devices
- D. VM Storage Policies

Correct Answer: A

With NAS storage devices, the hardware acceleration integration is implemented through vendorspecific NAS plug-ins. These plug-ins are typically created by vendors and are distributed as VIB packages through a website. No claim rules are required for the NAS plug-ins to function. Several tools for installing and upgrading VIB packages are available. They include the esxcli commands and vSphere Update Manager.

QUESTION 12

Which method is supported for backing up the virtual machine that contains vCenter Server?

- A. incremental
- B. individual disks
- C. differential
- D. full image

Correct Answer: D

To Read the [Whole Q&As](#), please purchase the [Complete Version](#) from [Our website](#).

Try our product !

100% Guaranteed Success

100% Money Back Guarantee

365 Days Free Update

Instant Download After Purchase

24x7 Customer Support

Average **99.9%** Success Rate

More than **800,000** Satisfied Customers Worldwide

Multi-Platform capabilities - **Windows, Mac, Android, iPhone, iPod, iPad, Kindle**

Need Help

Please provide as much detail as possible so we can best assist you.

To update a previously submitted ticket:



 <p>One Year Free Update Free update is available within One Year after your purchase. After One Year, you will get 50% discounts for updating. And we are proud to boast a 24/7 efficient Customer Support system via Email.</p>	 <p>Money Back Guarantee To ensure that you are spending on quality products, we provide 100% money back guarantee for 30 days from the date of purchase.</p>	 <p>Security & Privacy We respect customer privacy. We use McAfee's security service to provide you with utmost security for your personal information & peace of mind.</p>
---	---	--

Any charges made through this site will appear as Global Simulators Limited.

All trademarks are the property of their respective owners.